

CAW & CCW DOUBLE BOLT SERIES

The CCW and CAW series of connectors have been specially designed to provide a waterproof connection between insulated overhead services to a variety of bare overhead mains. Both single and double tap models are available.



CCW35DBE

CCW35DB

Product Number	Mains Range			Service Taps		Pack Size (pcs)
	Stranding	Area (mm ²)	OD (mm)	Range (mm ²)	Quantity	
Connectors for Bare Copper Mains						
CCW35DB	7/1.00 to 19/3.00 Cu	5.5 to 135	3 to 15	6 to 35	2	6
CCW35DBE	7/1.00 to 19/3.00 Cu	5.5 to 135	3 to 15	6 to 35	2	6

CCW DOUBLE BOLT SERIES

APPLICATION

Mains: Bare copper
Service: Insulated copper or aluminium

FEATURES

- + Piercing connector on service tap
- + Disconnection of service by easy removal of the connector from the mains
- + Service connection fully sealed and waterproof
- + Bimetallic service connection, tin plated brass teeth
- + Transparent window ensures cable is correctly inserted

INSTALLATION NOTES

Use only a 13mm AF, six point hexagon socket to tighten bolts.

All other connections made on the service and consumers cable must also be waterproof to prevent moisture ingress through the cable into the connector.



CAW35DBE

CAW35DB

Product Number	Mains Range			Service Taps		Pack Size (pcs)
	Stranding	Area (mm ²)	OD (mm)	Range (mm ²)	Quantity	
Connectors for Bare Aluminium Mains						
CAW35DB	7/1.75 to 19/3.75 Al	16 to 210	5 to 19	6 to 35	2	6
CAW35DBE	7/1.75 to 19/3.75 Al	16 to 210	5 to 19	6 to 35	2	6

CAW DOUBLE BOLT SERIES

APPLICATION

Mains: Bare aluminium
Service: Insulated copper or aluminium

FEATURES

- + Piercing connector on service tap
- + Disconnection of service by easy removal of the connector from the mains
- + Service connection fully sealed and waterproof
- + Bimetallic service connection, tin plated brass teeth
- + Transparent window ensures cable is correctly inserted

INSTALLATION NOTES

Use only a 13mm AF, six point hexagon socket to tighten bolts.

All other connections made on the service and consumers cable must also be waterproof to prevent moisture ingress through the cable into the connector.

PLEASE NOTE: The products on this page can be ordered with high visibility shear-off identification tags. To order the products with these identification tags please add the suffix **E** to the end of the product number when ordering.



Recommended tool for all products: RPS13/17-6H or RPS13/17-6SH

