

Product data sheet

Characteristics

1025USBC-ZW

Double Switch Power Point, Clipsal Solis,
 Double Switch Power Point with USB C
 Charger, Horizontal Mount, 230V-240V, 10A



Main

Product or component type	Switched socket with USB charger
Assembly Type	Complete product
Standards	AS/NZS 3112
Product certifications	RCM
Main colour tint	Matt white

Complementary

Range	Clipsal Solis
Number Of Outlets	2
Device mounting	Wall mounted 65 mm
Cover type	With shutter
Number of power socket outlets	2 x 2P + E, Australian/New Zealand
Rated current	10 A 230/240 V, AC, 50 Hz
Connections - terminals	4 x 2.5 mm ² screw terminals 3 x 4 mm ² screw terminals
Colour tint	Matt white
Surface finish	Matt
Surface treatment	Painted
Additional Function	USB type C
Material	Plastic
Screwdriver shape	Philips No 2 Square drive no 1 (SQ1)
Wire stripping length	16 mm
Fixing mode	By screw
Fixing center	120 mm
Height	74 mm
Width	148 mm
Depth	69.5 mm
Sale per indivisible quantity	1
Installation Type	Flush
Installation Orientation	Horizontal
Control type	Rocker
Cover Thickness	4.5 mm
Cut-out dimensions	130 x 50 mm
Number Of Switches	2

Environment

Ambient air temperature for operation	0...45 °C
Relative humidity	10...95 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.5 cm
Package 1 Width	8 cm
Package 1 Length	8 cm
Package 1 Weight	233 g
Unit Type of Package 2	CAR
Number of Units in Package 2	30
Package 2 Height	32.5 cm
Package 2 Width	25 cm
Package 2 Length	41 cm
Package 2 Weight	7.37 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	No need of specific recycling operations