

Product data sheet

Characteristics

1025XUA-LB

Double Switch Power Point, Clipsal Solis T Series, Horizontal Mount, 230V-240V, 10A, Removable Extra Switch



Main

| | |
|---------------------------|------------------------|
| Range | Clipsal Solis T Series |
| Product or component type | Switched socket |
| Product brand | Clipsal |
| Assembly Type | Complete product |
| Colour tint | Living brass |
| Protection | Shuttered |
| Main colour tint | Living brass |

Complementary

| | |
|--------------------------------|--|
| Control type | Rocker |
| Number Of Outlets | 2 |
| Socket-outlet type | Double socket-outlet |
| Mounting Type | Screw |
| Installation Type | Flush |
| Installation Orientation | Horizontal |
| Material | Brass |
| Surface finish | Metallic |
| [Ue] rated operational voltage | 230/240 V AC |
| Network frequency | 50 Hz |
| [In] rated current | 10 A |
| Connections - terminals | 4 x 2.5 mm ² screw terminals 3 x 4 mm ² screw terminals |
| Embedding depth | 23.5 mm |
| Depth | 27.4 mm |
| Height | 74 mm |
| Width | 148 mm |
| Mounting Centers | 120 mm |
| Cut-out dimensions | 130 x 50 mm |
| Surface treatment | Painted |
| Screwdriver shape | Philips No 2 Square drive no 1 (SQ1) |
| Wire stripping length | 16 mm |
| Number of power socket outlets | 2 x 2P + E, Australian/New Zealand |
| Cover Thickness | 5 mm |
| Number Of Switches | 2 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

| | |
|---------------------------------------|-------------|
| Product certifications | RCM |
| Standards | AS/NZS 3112 |
| Relative humidity | 10...95 % |
| Ambient air temperature for operation | 0...45 °C |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 15.5 cm |
| Package 1 Width | 6 cm |
| Package 1 Length | 8 cm |
| Package 1 Weight | 272 g |
| Unit Type of Package 2 | CAR |
| Number of Units in Package 2 | 40 |
| Package 2 Height | 32.5 cm |
| Package 2 Width | 25 cm |
| Package 2 Length | 41 cm |
| Package 2 Weight | 11.26 kg |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |