

## Product data sheet

### Characteristics

# 1044TA-EA

## Flush Switch, Clipsal Solis T Series, Horizontal Mount, 4 Gang, 230V-240V, 10AX 1-Way/2-Way



### Main

|                           |                        |
|---------------------------|------------------------|
| Range                     | Clipsal Solis T Series |
| Product brand             | Clipsal                |
| Product or component type | Switch                 |
| Assembly Type             | Complete product       |
| Outlet standard deviation | Australian/New Zealand |
| Colour tint               | Ebony aluminium        |

### Complementary

|                                |   |
|--------------------------------|---|
| Number of gangs                | 4 gangs                                 |
| [Ue] rated operational voltage | 230/240 V                               |
| Network type                   | AC                                      |
| Network frequency              | 50 Hz                                   |
| Rated current                  | 20 A/16 AX                              |
| Control type                   | Toggle switch                           |
| Connections - terminals        | Screw terminals                         |
| Installation Type              | Flush                                   |
| Number Of Switches             | 4                                       |
| Material                       | Aluminium                               |
| Installation direction         | Horizontal                              |
| Surface treatment              | Metallic                                |
| Load type                      | LEDi lamp 0...250 W 20 A/16 AX          |
| Terminals Capacity             | 4 x 1.5...3 x 2.5 mm <sup>2</sup>       |
| Screwdriver shape              | Philips No 2<br>Square drive no 1 (SQ1) |
| Wire stripping length          | 10 mm                                   |
| Mounting Type                  | Screw                                   |
| Cover Thickness                | 3.6 mm                                  |
| Mounting Centers               | 120 mm                                  |
| Cut-out dimensions             | 130 x 50 mm                             |
| Product certifications         | RCM                                     |
| Surface finish                 | Aluminium                               |
| Height                         | 74 mm                                   |
| Width                          | 148 mm                                  |
| Depth                          | 56 mm                                   |
| Embedding depth                | 41 mm                                   |
| Motor M-rating AS3133          | M80                                     |
| Switch function                | 1-pole 1/2-way                          |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

|                                       |              |
|---------------------------------------|--------------|
| Ambient air temperature for operation | 0...45 °C    |
| Relative humidity                     | 10...95 %    |
| Standards                             | AS/NZS 60669 |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 15.5 cm  |
| Package 1 Width              | 8 cm     |
| Package 1 Length             | 8 cm     |
| Package 1 Weight             | 160 g    |
| Unit Type of Package 2       | CAR      |
| Number of Units in Package 2 | 30       |
| Package 2 Height             | 34 cm    |
| Package 2 Width              | 36 cm    |
| Package 2 Length             | 48 cm    |
| Package 2 Weight             | 4.884 kg |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product                         |
| REACH Regulation           | <a href="#">REACH Declaration</a>             |
| EU RoHS Directive          | Compliant with Exemptions                     |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>                           |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>        |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a> |
| Circularity Profile        | No need of specific recycling operations      |