

Product data sheet Characteristics

4061D32-PW

Switch Saturn - Assembled - Cooker - Doublepole - 415 V - 32 A - Pure White



Main

| Range of product | Saturn Series 4000 |
|---------------------|--------------------|
| Product brand | Clipsal |
| Device presentation | Basic element |

Complementary

| Switch function | 2-pole | |
|--------------------------------|-----------------|--|
| Number of poles | 2 | |
| Device mounting | Flush | |
| Fixing mode | By screws | |
| Local signalling | without | |
| [Ue] rated operational voltage | 415 V AC | |
| Rated current | 32 A | |
| Marking | Without marking | |
| Height | 116 mm | |
| Width | 75 mm | |
| Depth | 37 mm | |
| Embedding depth | 23 mm | |
| | | |

Packing Units

| r doming office | | |
|------------------------------|--------|---|
| Unit Type of Package 1 | PCE | |
| Number of Units in Package 1 | 1 | : |
| Package 1 Weight | 234 g | |
| Package 1 Height | 90 mm | |
| Package 1 width | 62 mm | - |
| Package 1 Length | 120 mm | |
| | | |

Offer Sustainability

| EU RoHS Directive | Under investigation |
|--------------------------|-------------------------------|
| Environmental Disclosure | Product Environmental Profile |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.