

## Product data sheet

### Characteristics

# 56C532-GY

## 56 Series switched socket surface IP66 5 pin 32 A - Grey



### Main

|                           |                     |
|---------------------------|---------------------|
| Range of product          | Series 56           |
| Range                     | Clipsal - 56 Series |
| Product brand             | Clipsal             |
| Product or component type | Socket-outlet       |
| Device application        | Power supply        |
| Colour                    | Grey (RAL 7035)     |

### Complementary

|                                     |   |
|-------------------------------------|---|
| Number of poles                     | 5   |
| Plug, socket category               | Low voltage                                     |
| Outlet standard                     | Australian/New Zealand                          |
| Plug, socket, control station shape | Straight  |
| Number of modules                   | 3   |
| Number of power socket outlets      | 1 protective cover                              |
| [In] rated current                  | 32 A  |
| [Ue] rated operational voltage      | 500 V AC 50 Hz                                  |
| Poles description                   | 3P + N + E                                      |
| Protection type                     | Without protection                              |
| Device mounting                     | Surface   |
| Material                            | Polycarbonate: cover                            |
| Contacts material                   | Pins: phosphor bronze                           |
| Connections - terminals             | Screw terminals cable(s) 4...16 mm <sup>2</sup> |
| Electrical connection               | Industrial connector                            |
| Depth                               | 108 mm  |
| Width                               | 101 mm  |
| Height                              | 204 mm  |
| Targeted country                    | Australia                                       |

### Environment

|                                       |                             |
|---------------------------------------|-----------------------------|
| Standards                             | AS/NZS 3133<br>AS/NZS 3123  |
| Ambient air temperature for operation | -25...75 °C                 |
| IP degree of protection               | IP66 conforming to AS 60529 |

### Packing Units

|                  |            |
|------------------|------------|
| Package 1 Weight | 1.100 kg   |
| Package 1 Height | 108.000 mm |
| Package 1 width  | 101.000 mm |
| Package 1 Length | 204.000 mm |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product                         |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>                           |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>        |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a> |