

Product datasheet

Specifications



LED Downlight, Airflow, 7W, 45dB

CPL7600ATP-WE



Main

Range of product	Airflow
Range	Airflow
Product brand	Clipsal
Product or component type	Fan, Light and Heater units
Product destination	Ceiling fitting
Device application	Duct
Main colour tint	White
Colour tint	White

Complementary

[Ue] rated operational voltage	230/240 V AC 50 Hz
air flow	300 m ³ /h
Power consumption in W	590 W
Cut-out dimensions	470 x 270 mm
Depth	200 mm
Air discharge option	Downflow
Noise level	45 dB
Fan type	Centrifugal
Light source	LED 7 W
Heat dissipation	275 W

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	43 cm
Package 1 Width	33 cm
Package 1 Length	53.7 cm
Package 1 Weight	6.3 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	12
Package 2 Height	110 cm

Package 2 Width	114 cm
Package 2 Length	114 cm
Package 2 Weight	90.6 kg



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) **3287**

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard **No**

Packaging without single use plastic **No**

EU RoHS Directive **Compliant with Exemptions**

REACH Regulation [REACH Declaration](#)

China RoHS Regulation [China RoHS declaration](#)

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

WEEE  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Take-back **No**