


# Product datasheet

Specifications



## Circular LED, Clipsal - Lighting, 17W, 1700lm, IP54, white

CLITPCLS

### Main

Range	Clipsal
Product or component type	Ceiling light
Device application	Lighting
Market segment	Residential Small commercial

### Complementary

type of installation	Indoor
Total system power	17 W
Light source	LED
[Ue] rated operational voltage	230/240 V AC 50 Hz
Colour rendering index	R <sub>a</sub> =80
Luminous flux	1700 lm
Bulb lifespan	50000 h
Colour temperature	3000 K 4000 K 5700 K
Beam angle	110 °
Device mounting	Ceiling
Mounting mode	Surface mounted
Device composition	Base white Diffuser white opal
Shape	Round
Height	23 mm
Diameter	294 mm
Targeted country	Australia New Zealand
Colour tint	White
Main colour tint	White

### Environment

IP degree of protection	IP54
IK degree of protection	IK02
Ambient air temperature for operation	0...40 °C

---

Relative humidity	10...95 % non-condensing
-------------------	--------------------------

## Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Number of Units in Package 1	1
------------------------------	---

---

Package 1 Height	30 cm
------------------	-------

---

Package 1 Width	2.8 cm
-----------------	--------

---

Package 1 Length	30 cm
------------------	-------

---

Package 1 Weight	710 g
------------------	-------

---

Unit Type of Package 2	CAR
------------------------	-----

---

Number of Units in Package 2	6
------------------------------	---

---

Package 2 Height	35 cm
------------------	-------

---

Package 2 Width	21.3 cm
-----------------	---------

---

Package 2 Length	34 cm
------------------	-------

---

Package 2 Weight	4.884 kg
------------------	----------

---

Unit Type of Package 3	PAL
------------------------	-----

---

Number of Units in Package 3	192
------------------------------	-----

---

Package 3 Height	110 cm
------------------	--------

---

Package 3 Width	114 cm
-----------------	--------

---

Package 3 Length	114 cm
------------------	--------

---

Package 3 Weight	170.288 kg
------------------	------------

## Contractual warranty

---

Warranty	5 Years
----------	---------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) 15

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

China RoHS Regulation [China RoHS declaration](#)

## Use Again

### Repack and remanufacture

Circularity Profile [End of Life Information](#)

Halogen content performance Halogen free plastic parts product

Take-back No