

## Product data sheet

### Characteristics

# CLITPDL1C3R

Downlight, Clipsal - Lighting, 750lm, 3K/4K/6K, ripple resistant filtering, white



### Main

Range	Clipsal
Product or component type	Downlight
Market segment	Residential
Main colour tint	White
Colour tint	White

### Complementary

Device mounting	Ceiling
Rated power in W	7 W
Light source	LED
Total system power	230/240 V AC 50 Hz
Luminous flux	750 Lm 3000 K 750 Lm 4000 K 750 lm 6000 K
Colour rendering index	R <sub>a</sub> =80
Bulb lifespan	50000 h
Beam angle	110 °
Trim width	110 mm
Trim height	55 mm
Cut-out dimensions	90 mm
Mounting depth	55 mm
Net weight	200 g

### Environment

IP degree of protection	IP44
IK degree of protection	IK02
Insulation contact rating	IC-4
Unified glare rating	< 22

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9 cm
Package 1 Width	13 cm
Package 1 Length	13 cm
Package 1 Weight	264 g
Unit Type of Package 2	CAR
Number of Units in Package 2	24

Package 2 Height	30 cm
Package 2 Width	27.5 cm
Package 2 Length	54 cm
Package 2 Weight	6.972 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	576
Package 3 Height	110 cm
Package 3 Width	114 cm
Package 3 Length	114 cm
Package 3 Weight	188 kg

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
Halogen content performance	Halogen free plastic parts product

### Contractual warranty

Warranty	3 Years
----------	---------