Specifications

**CLIPSAL** 



## Downlight, Clipsal - Lighting, 750lm, recessed low glare, black

CLITPDLLGBK

#### Main

Range	Clipsal
Product or component type	Downlight
Market segment	Residential
Main colour tint	Black
Colour tint	Black

## Complementary

e emprementar y		
Device mounting	Ceiling	
Rated power in W	7 W	
Light source	LED	
Total system power	230/240 V AC 50 Hz	
Luminous flux	800 lm 3000 K 800 lm 4000 K 800 lm 6000 K	
Colour rendering index	R <sub>a</sub> =80	
Bulb lifespan	35000 h	
Beam angle	60 °	
Trim width	103 mm	
Trim height	86 mm	
Cut-out dimensions	90 mm	
Mounting depth	86 mm	
Product weight	190 g	

#### Environment

IP degree of protection	IP44
IK degree of protection	IK02
Insulation contact rating	IC-4
Unified glare rating	< 22

#### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10 cm

Package 1 Width	11 cm
Package 1 Length	11 cm
Package 1 Weight	283 g
Unit Type of Package 2	CAR
Number of Units in Package 2	20
Package 2 Height	23.3 cm
Package 2 Width	24.2 cm
Package 2 Length	57.9 cm
Package 2 Weight	6.141 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	640
Package 3 Height	110 cm
Package 3 Width	114 cm
Package 3 Length	114 cm
Package 3 Weight	210.512 kg

## **Contractual warranty**

Warranty

3 Years

## 🜔 Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

# Image: Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) 6 Environmental Disclosure Product Environmental Profile

#### **Use Better**

S Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
China RoHS Regulation	China RoHS declaration

#### Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Halogen content performance	Halogen free plastic parts product
Take-back	No