

Product datasheet

Specifications

CLIPSAL



Batten Toughend LED, Clipsal -
Lighting, 10W, 600mm, 3000K /
4000K / 6500K, IP65, IK08, white

CLITPTUFF600

Main

Range	Clipsal
product name	TPWP Series
Product or component type	Batten light
Device application	Lighting

Complementary

type of installation	Outdoor
Total system power	10 W
[Ue] rated operational voltage	230/240 V AC 50 Hz
Colour rendering index	R _a =80
Luminous flux	1250 lm
Bulb lifespan	50000 h
Colour temperature	3000 K 4000 K 5700 K
Mounting mode	Ceiling
Electrical insulation class	Class II
Light source	LED
Shape	Rectangular
Height	120 mm
Width	95 mm
Length	680 mm
Product weight	1500 g
Colour tint	White

Environment

IP degree of protection	IP65
IK degree of protection	IK08
Relative humidity	10...95 %
Ambient air temperature for operation	-10...45 °C
Targeted country	Australia

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.9 cm
Package 1 Width	10.7 cm
Package 1 Length	71.3 cm
Package 1 Weight	1.731 kg
Unit Type of Package 2	CAR
Number of Units in Package 2	6
Package 2 Height	30.5 cm
Package 2 Width	36 cm
Package 2 Length	74.8 cm
Package 2 Weight	11.492 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	72
Package 3 Height	110 cm
Package 3 Width	114 cm
Package 3 Length	114 cm
Package 3 Weight	151.904 kg

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) 335

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant

REACH Regulation [REACH Declaration](#)

China RoHS Regulation [China RoHS declaration](#)

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Halogen content performance Halogen free plastic parts product

Take-back No