Specifications

CLIPSAL

Batten Weatherproof LED, Clipsal - Lighting, 36W, 1200mm, 3000K / 4000K / 6500K, IP65, IK08, white

CLITPWP1200

Main

mann	
Range	Clipsal
product name	TPWP Series
Product or component type	Batten light
Device application	Lighting

Complementary

complementary		
type of installation	Outdoor	
Total system power	36 W	
[Ue] rated operational voltage	230/240 V AC 50 Hz	
Colour rendering index	R _a =80	
Luminous flux	4500 lm	
Bulb lifespan	50000 h	
Colour temperature	3000 K 4000 K 5700 K	
Mounting mode	Ceiling	
Electrical insulation class	Class II	
Light source	LED	
Shape	Rectangular	
Height	80 mm	
Width	100 mm	
Length	1240 mm	
Net weight	1600 g	
Colour tint	White	

Environment

IP degree of protection	IP65
IK degree of protection	IK08
Relative humidity	1095 %
Ambient air temperature for operation	-1045 °C
Targeted country	Australia

Packing Units

Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.15 cm
Package 1 Width	11.15 cm
Package 1 Length	129.8 cm
Package 1 Weight	2.049 kg
Unit Type of Package 2	CAR
Number of Units in Package 2	6
Package 2 Height	21.6 cm
Package 2 Width	37.1 cm
Package 2 Length	133.3 cm
Package 2 Weight	13.748 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	72
Package 3 Height	110 cm
Package 3 Width	114 cm
Package 3 Length	135 cm
Package 3 Weight	187.976 kg

C Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability \geq

P Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	243
Environmental Disclosure	Product Environmental Profile

Use Better

S Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
China RoHS Regulation	China RoHS declaration

Use Again

\circlearrowright Repack and remanufacture	
Circularity Profile	End of Life Information
Halogen content performance	Halogen free plastic parts product
Take-back	No