Batten Weatherproof LED, Clipsal - Lighting, 18W, 600mm, 3000K / 4000K / 6500K, IP65, IK08, white

CLITPWP600

Main

Range	Clipsal
product name	TPWP Series
Product or component type	Batten light
Device application	Liahtina

Complementary

type of installation	Outdoor	
Total system power	18 W	
[Ue] rated operational voltage	230/240 V AC 50 Hz	
Colour rendering index	R _a =80	
Luminous flux	2250 lm	
Bulb lifespan	50000 h	
Colour temperature	3000 K 4000 K 5700 K	
Mounting mode	Ceiling	
Electrical insulation class	Class II	
Light source	LED	
Shape	Rectangular	
Height	80 mm	
Width	100 mm	
Length	640 mm	
Product weight	1000 g	
Colour tint	White	

Environment

IP degree of protection	IP65
IK degree of protection	IK08
Relative humidity	1095 %
Ambient air temperature for operation	-1045 °C
Targeted country	Australia

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.15 cm
Package 1 Width	11.15 cm
Package 1 Length	69.8 cm
Package 1 Weight	1.098 kg
Unit Type of Package 2	CAR
Number of Units in Package 2	6
Package 2 Height	21.6 cm
Package 2 Width	37.1 cm
Package 2 Length	73.3 cm
Package 2 Weight	7.553 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	96
Package 3 Height	110 cm
Package 3 Width	114 cm
Package 3 Length	114 cm
Package 3 Weight	134.848 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	328
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
China RoHS Regulation	China RoHS declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Halogen content performance	Halogen free plastic parts product
Take-back	No