

## Connectors - R Series



**Weight:** 0.00kg

**Dimensions:** 0.00cm x 0.00cm x 0.00cm

### Description

This range of product provides for XPLE or PVC copper or aluminium service cable connection to bare copper and bare aluminium mains in a complete moisture free environment. The service connection is made with insulation piercing technology where there is no need to strip the cable.

### Features

- Copper connector has forged body for added strength.
- All tested to applicable requirements of AS/NZS4396.
- Both mains and tap bolts incorporate shearhead technology for use with a standard M8 socket.
- Polycarbonate windows employed on all tap facilities to ensure the operator can see the actual connection.
- Single and double bolt versions

### Documentation

[Trade Catalogue](#) see p.10 - p.17

### Part Tables

Part Number	Material Type	Bare Mains Range	Area mm <sup>2</sup>	O.D. mm	Tap Range mm <sup>2</sup>
R235	Copper	7/1.00 - 19/3.00	5.5 - 135	3 - 15	6 - 35
R235-4	Copper	7/1.00 - 19/3.00	5.5 - 135	3 - 15	6 - 35

Part Number	Material Type	Bare Mains Range	Area mm <sup>2</sup>	O.D. mm	Tap Range mm <sup>2</sup>
R236	Aluminium	7/1.75 - 19/3.75	16 - 210	5 - 19	6 - 35
R236-4	Aluminium	7/1.75 - 19/3.75	16 - 210	5 - 19	6 - 35

## Product Gallery

